

GENERAL DATA	
Туре	Crew boat
Year built / builder	2010, Topaz Shipbuilding,
	Fujairah, UAE
Class	(RMRS) KM 🕏 R2
Flag	Azerbaijan
Port of registry	Baku
Call sign	4JNZ
IMO number	9581538

PIPE LAY CAPABILITIES	
Length overall	35.0 m
Breadth	7.50 m
Summer Draft	1.9 m
Max Draft	
(protruding of propellers)	2.4 m
Freeboard at Summer Draft	1.516 m
Gross Tonnage	200 t
Net Tonnage	60 t
Deadweight max	93 t
Deck Working area	134.5 m2
Deck Strength	2 t/m2
Deck Cargo Capacity	50 t

36,246 m3

15,666 m3

**CAPACITIES**Fuel Oil

Fresh Water

PROPULSION	
Main Engines	3 x CAT C32 1081kw@2300rpm
Gearboxes	3 x Twin Disc MGX 6650 SC, 2.93:1
Propellers	3 x Teignbridge five blade propellers
Bow thruster	Thrustmaster 37 kW Hydraulic
	16TT50L

AUXILIARIES	
Auxiliary set	2 x CAT C4.4 107 KVA, 50 Hertz
Generators	415 VAC, 3 phase, 50Hz, 4 wires
Voltage	240 V AC, 1 phase, 50 Hz, 3 wires
Frequency	24 V DC circuit

SPEED	
Maximum	16.5 knots
Economical	11 knots

FUEL CONSUMPTION PER DAY		
Full Speed	9 м³	
Economical	6.6 м <sup>3</sup>	

NAVIGATION EQUIPMENT	
Radar	1 x Koden Radar
Echo Sounder	1 x F-3000W
Auto Pilot	1 x ALPHASEAPILOT MFC
Doppler Log	1 x NAVIKNOT 450 D
Navtex receiver	1 x Model NT-2000
GPS	1 x GPS plotter HGP 660

# **COMMUNICATION EQUIPMENT**

MF/HF Transceiver Sailor CU5100 MF/HF Control Unit

GMDSS SS1 x INMARSAT MMSI

423335100, Inmarsat C, Area 1

VHF 1 x ICOM M-604,1 x SAMYUNG

STR-6000A

# **LIFESAVING APPLIANCES**

Life Rafts 6 x 25 man

Lifejackets 69 (2 pcs for personnel on watch)

Immersion Suits 10 pcs
Rescue Boat 1 x 6 man

### **FIFI EQUIPMENT**

Fixed system CO2
BA sets x2

### **ACCOMMODATION**

Cabins: Crew cabins 5 cabins. 2 single, 3 double cabins

Berth (Total) 8

Crew **8 persons**Passengers **54 persons** 

### **MOORING EQUIPMENT**

Anchor 2 x Super High Holding Power

136.8 kg

Anchor chain Grade 2 stud chain, breaking

strength 151kN

Anchor winch 2 x HHAW 15-16, reel type, electro

hydraulic

### **CRANE**

1 x FASSI 1.075 T @ 10.05m

#### **VESSEL SPECIFIC CHARACTERISTICS**

"Gulustan" is a multipurpose vessel, able to transport 54 passengers plus crew and up to 50 tons of deck cargo at maximum speed of 16.5 knots. The knuckle / HIAB boom crane installed mid-ships on the port side allows materials to be quickly and easily transferred to or from the vessel. The deck area has been so arranged that 3 standard 20" containers can be carried. Passengers are seated in a dedicated lounge in airline style seats and provided with an AV entertainment system so safety briefings can be observed prior to arriving at destination. Passenger transfer to installation can be achieved by Frog 3, basket transfer or direct access. Three fixed pitch propellers and additional bow tunnel thruster allowing excellent maneuverability and station keeping potential.

Additionally the Gobustan is equipped with an engine driven (middle engine) firefighting pump supplying a single monitor positioned on the stbd aft quarter, the pump supplies 600 m3/hr. at 10 bar giving a reach of 110 meters. Highlighted by the red circle below.





